

Parameter Parameter	B Type PTV (Patient
	Transport Vehicle)
Wheel Base	2815mm
Emission Norm	BS6
Engine Capacity	3455cc
Engine Power	75 kW @ 2600 rpm
Engine Torque	315 Nm @ 1400-1600 rpm
Power Steering	<b>√</b>
No. of Tyres	4+1
Air Conditioning in Patient Compartment	Optional
Air Conditioning in Driver's Cabin	×
Overall Length mm	5579
Overall Width mm	2000
Automatic Roll-In stretchers	Yes, Qty – 1 or 2
	Compliant to Type-B
Bar Light & Public Address System	×
Revolving Light on top	√, Blue Beacon Light
Side Blinkers & Flood Lights	X
Dual Battery	×
Provision/Space for Medical Equipment	<b>√</b>
220 V Power Supply External Charging Arrangement With Invertor	×

Extra Fitment (Not in Part-1 of AIS-125)	
Oxygen Delivery System	

Oxygen Delivery System	√, Clamp for mounting Cylinders
IV Bottle Hooks/Space	$\checkmark$
Scoop Stretcher	×
Spine Board	×

- External Graphics as per ambulance code. Medical Equipment/Medicines are NOT Included in the Standard SML Supply Scope. Provision/Space will be provided
- Oxygen Cylinders are not Included. Auto Changer Oxygen Supply System with Digital Display is available at Extra cost (for D type)

Disclaimer: The specifications may change without any prior notice, as per the company's policy of continues improvement of its products/services. The pictures used are for indicative illustration purpose only, actual product may vary. All cargo dimensions are for quick reference purpose only.















## SML ISUZU LTD.

Corporate Office: 204-205, Sector 34-A, Chandigarh-160022 Website: www.smlisuzu.com

Visit Us: f @smlisuzuoffical @@smlisuzuofficial f @company/sml-isuzu-ltd













Missed Call at 9319871155



Send "Hi" message on Whatsapp #9988224365



Type bit.ly/SMLISUZU on web browser

