

MEDICAL CARE, RELIABILITY & EXCELLENCE AT ITS BEST



Fully Compliant to
National Ambulance Code
AIS-125 (Part-1)



Single/Double Auto
Loading Stretcher Option



External Power support for
stationary use and charging
inverter. (C&D)

AIS-125

GS AMBULANCE

D TYPE

Parameter	D Type ALS (Advance Life Support)
Wheel Base	2815mm
Emission Norm	BS6
Engine Capacity	3455cc
Engine Power	75 kW @ 2600 rpm
Engine Torque	315 Nm @ 1400-1600 rpm
Power Steering	✓
No. of Tyres	4+1
Air Conditioning in Patient Compartment	✓
Air Conditioning in Driver's Cabin	✓
Overall Length mm	5579
Overall Width mm	2000
Automatic Roll-In stretchers	Yes, Qty – 1 or 2 Compliant to Type-D
Bar Light & Public Address System	✓
Revolving Light on top	✗, Part of Bar Light
Side Blinkers & Flood Lights	✓
Dual Battery	✓
Provision/Space for Medical Equipment	✓
220 V Power Supply External Charging Arrangement With Invertor	✓
Extra Fitment (Not in Part-1 of AIS-125)	
Oxygen Delivery System	✓, with Compartment for 02 Cylinders
IV Bottle Hooks/Space	✓
Scoop Stretcher	Optional
Spine Board	Optional

• External Graphics as per ambulance code. • Medical Equipment/Medicines are NOT Included in the Standard SML Supply Scope. Provision/Space will be provided
• Oxygen Cylinders are not Included. • Auto Changer Oxygen Supply System with Digital Display is available at Extra cost (for D type)

Disclaimer : The specifications may change without any prior notice, as per the company's policy of continuous improvement of its products/services. The pictures used are for indicative illustration purpose only, actual product may vary. All cargo dimensions are for quick reference purpose only.

